

ステンレスパンチングメタル 1000×2000

鋼種	孔径×ピッチ	配列	開口率 %	0.3t	0.4t	0.5t	0.6t	0.8t	1.0t	1.2t	1.5t	2.0t	3.0t	4.0t	5.0t
SUS 304	0.5φ×1p	60度千鳥	23	2B○	2B○										
	0.8φ×1.5p	60度千鳥	26				BA○								
	1φ×2p	60度千鳥	23			BA○		BA○	BA○						
	1.5φ×3p	60度千鳥	23			○		○	○	○	2B○				
	2φ×3p	60度千鳥	40			○			○		2B○				
	2φ×3.5p	60度千鳥	30			○	○	○	○	○	○				
	2φ×4p	60度千鳥	23									2B○			
	2.5φ×4p	60度千鳥	35						○						
	3φ×4p	60度千鳥	51			○		○	○		2B○	2B○			
	3φ×5p	60度千鳥	33		○	○	○	○	○	○	○	2B○	No.1○		
	4φ×6p	60度千鳥	40						○		○				
	4φ×7p	60度千鳥	30					○	○	○	○	2B○			
	5φ×6p	60度千鳥	63						○						
	5φ×8p	60度千鳥	35			○	○	○	○	○	○	2B○	2B○		
	6φ×8p	60度千鳥	51						○		○				
	6φ×9p	60度千鳥	40				○	○	○	○	○	2B○			
	8φ×10p	60度千鳥	58				○	○	○	○	○	2B○			
	8φ×12p	60度千鳥	40					○	○		○	2B○	2B○		
	10φ×15p	60度千鳥	40				○	○	○	○	○	2B○	2B○	No.1○	No.1○
	12φ×18p	60度千鳥	40								○				
15φ×20p	60度千鳥	51						○	○	○	2B○				
20φ×30p	60度千鳥	40								○	2B○				
○十	千鳥	30	○	○				○	○		○				
8□×10p	並列	64							○						
3×20 雲	千鳥	33						○							
4×25 雲	並列	46						○							

※表面仕上げ=○印のみのものは、片面#400研磨です。